

## Flex II FlashReader

Part Number: FSR-FR01

CAW	Version 9.4 (or newer)
Enterprise	<input checked="" type="checkbox"/>
Basic	<input type="checkbox"/>

The Flex II FlashReader is an input device for the CyberLock Flex II wired access control system. It connects to a Flex II Controller or Door Expander to open an electric door strike. A user can gain access by presenting credentials such as RFID cards, or a cell phone using CyberLock's Flash technology. When using Flash technology credentials are presented via a user's smartphone display meaning no app is required and access can be facilitated with a text or email message.

### Specifications

<b>Physical</b>	Fiberglass Reinforced Nylon
<b>Operating Temperatures</b>	-40° to 140° F (-40° to 60° C)
<b>Humidity</b>	0 to 100%
<b>Dimensions</b>	4.8" L x 1.7"W x 1.14" D (122 mm x 43 mm x 29 mm)
<b>Weight</b>	4.4 oz (125 g)
<b>Mounting</b>	Flush mount to a surface or single gang box using included mounting bracket, 2X #6 screws recommended
<b>Power</b>	Via RS485, CAT 5 patch cable from Flex II Controller or Door Expander
<b>Connections</b>	RJ45
<b>Credentials</b>	Smartphone enabled Flash Technology, RFID Cards Type A and I 5693 formats
<b>Visual Indicator</b>	3 multicolored LED indicator lights
<b>Audio Indicator</b>	Beeper
<b>Ingress Protection</b>	IP66
<b>RoHS</b>	Compliant with EU 2015/863

