

CyberKey X2C Control Key

Part Number: CKR-X2C



| CAW | Version 9.5 or newer |
|------------|-------------------------------------|
| Enterprise | <input checked="" type="checkbox"/> |
| Basic | <input checked="" type="checkbox"/> |

The RoHS compliant CyberKey X2C is for installing and removing CyberLock interchangeable core cylinders including CL-SF03, CL2-SF03, CL-LF01, and CL2-LF01. The control key must be programmed to open the cylinders it will be installing or removing. The CKR-X2C is not compatible with other CyberLock cylinders.

CKR-X2C has a replaceable battery and is fully compatible with all Gen 2 CyberLock features.

Specifications

| | |
|------------------------------|--|
| Physical | Fiberglass reinforced nylon, replaceable stainless-steel tip |
| Operating Temperature | 32° to 122° F (0° to 50° C) |
| Weight | 1.5 oz (43.1 g) |
| Visual Output | Green indicator light |
| Sound Output | Embedded speaker |
| Power | 3V lithium CR2 battery, field replaceable |
| Memory | 2 MB for up to 12,000 audit trail events and up to 12,000 locks with Lock List expansion SEM |
| Compatibility | USB Station with CyberLink 2, IR Encoder I/O, CyberKey Web Authorizer Hub 2, and Flex II with a keyport. |
| RoHS | Compliant with EU 2015/863 |

